(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



. 1 COLI I ALIAN ILLA GILLA COLI CILLA COLI COLI COLI COLI COLI COLI COLI CILLA COLI CILLA COLI CILLA COLI CIL

(43) International Publication Date 6 May 2005 (06.05.2005)

PCT

(10) International Publication Number WO 2005/040656 A1

(51) International Patent Classification⁷: 31/08

F16K 31/06,

(21) International Application Number:

PCT/IB2004/003478

(22) International Filing Date: 22 October 2004 (22.10.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0324717.8

22 October 2003 (22.10.2003) GF

(71) Applicant (for all designated States except US): ELOPAK SYSTEMS AG [CH/CH]; Cherstrasse 4, Postfach, CH-8152 Glattbrugg (CH).

(72) Inventors: and


(75) Inventors/Applicants (for US only): LARSSON, Kalle

[SE/SE]; Lövangsvägen 21, S-25284 Helsingborg (SE). THINGELSTAD, Lars, Aksel [NO/NO]; Kønnerudgt. 10B, N-3045 Drammen (NO).

- (74) Agent: BURROWS, Anthony, Gregory; Business Centre West, Avenue One, Business Park, Hertfordshire, Letchworth Garden City SG6 2HB (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: A VALVE DEVICE FOR AND A METHOD OF CONTROLLING FLUID FLOW



(57) Abstract: A valve device (4) for controlling fluid flow comprises a hollow body (2) bounding a flow path through the valve device (4), a valve obturating member (10) in the flow path and movable between a fully obturating position and a less obturating position for permitting lesser and greater flows of fluid along the path, which flows urge the member (10) in the sense from the more obturating position to the less obturating position, the valve obturating member (10) including magnetic portions (18), and at least one electrically energizable inductor (22) fixed relative to the body (2) and serving to act upon the valve obturating member (10) to urge the valve obturating member (10) in the sense from the less obturating position to the fully obturating position.

GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

 before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.